



IRI.TX

TRANSMITTERS WITH DOUBLE CODING

4 channels



iride
passione italiana

BENINCA

100%
Made in Italy



Configuration and list of available channels (IRI.TX4VA, ARC only):

	CH1		CH5
	CH2		CH6
	CH3		CH7
	CH4		CH8
	hidden button		CH9



Training

Guide to the procedure of copying fixed codes, enabling ARC codes and changing coding. Watch the video.

- 4-channel transmitter with an elegant, refined design, made of high quality materials with distinctive finishing
- Front plastic parts have a double finish, which highlights the contrast between glossy and matt, and a metal key ring
- 12 V battery for long lifespan

AUTOMATISMI BENINCA SpA • Via del Capitello, 45 • 36066 Sandrigo (VI) ITALY • T +39 0444 751030 • sales@beninca.com




ONE.2WO

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code, Rolling Code and Fixed Code, with outdoor IP54 box. 512 memorisable codes.



ONE.2WB

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code and Rolling Code, in box. 512 memorisable codes.




ONE.2WI

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code and Rolling Code, plug-in. 512 memorisable codes.



ONE.4WB

4-channel receiver with full-range power supply (115-230 VAC/DC) and triple coding: Advanced Rolling Code, Rolling Code and Fixed Code, with outdoor IP54 box. 512 memorisable codes.



MEM2048

Additional memory for up to 2048 codes. For receivers of the ONE series.



AWO

433.92 MHz antenna for external installation with IP54 box, fitted with shielded RG58 5 m cable.



IRI.TX4VA

- 4-channel transmitter with double coding, Advanced Rolling Code and Rolling Code
- The new ARC coding guarantees maximum security due to the length of the transmitted code (128 bit) and the high number of possible combinations
- The transmitter has ARC coding as factory setting. However, it is possible to change the coding by using it in Rolling Code or even in mixed coding (ARC and Rolling Code)
- If using mixed coding, the ARC can be set with the T1/T3 buttons and the Rolling Code with the T2/T4 buttons
- The IRI.TX4VA model allows users to set up to 9 channels, thanks to the option of activating the command by simultaneously pressing two buttons chosen by the user. This function allows avoiding accidental openings caused by pressing a button by mistake and is particularly indicated for use with alarm systems



IRI.TX4AK

- 4-channel transmitter with double coding, Advanced Rolling Code and Fixed Code
- The new ARC coding guarantees maximum security due to the length of the transmitted code (128 bit) and the high number of possible combinations
- The transmitter allows expanding the convenience of remote duplication (without having access to the installation), typical of Fixed Codes, even with ARC.
- IRI.TX4AK transmitters can become duplicates of fixed code transmitters, but they can also be enabled to operate systems with Advanced Rolling Code
- It is possible to associate each button with different types of coding (Advanced Rolling Code or Fixed Code) independently
- Compatible with the most common fixed code transmitters

AUTOMATISMI BENINCÀ SpA • Via del Capitello, 45 • 36066 Sandrigo (VI) ITALY • T +39 0444 751030 • sales@beninca.com



RG58 MT5

AWO antenna cable
L = 5 m.



AW

433.92 MHz stylus antenna for external installation, equipped with a shielded 3m RG58 cable.



AF.S

Column fixing bracket for STAR flashing light and AW antenna. The accessory can also be used for the antenna only.



BT12

12 V Battery, for transmitter.
Available in 50 pcs packing.