























APPLICATION

1 or 2 actuators for tilt up doors

CONTROL UNIT POWER SUPPLY

100 ÷ 250 Vac - 50/60 Hz

MOTORS POWER SUPPLY

24 Vdc / 130 W + 130 W

POWER CONSUMPTION IN STAND-BY

0.8 W

MAIN FUNCTIONS

Integrated LCD display | Integrated radio receiver 433.92 MHz 64 codes with ARC coding | Removable terminal boards | Automatic, semi-automatic and Deadman logic | Encoder input | Step-by-step and stop inputs | Photocell input settable as input for N.C. or 8K2 sensitive edge | Two inputs configurable as open, close, photocell in opening-closing, photocell in closing, opening and closing limit switch for the second motor | Limit switch input | Separate power supply output for each motor | Output for 24 Vdc flashing light | 24 Vdc auxiliary output max 500mA Output (230Vac 5A max) configurable as open gate signal light, courtesy light, zone light, second radio channel, photocell testing, flashing light, open gate alarm, NC input alarm | 24 Vdc service light output | Autoset operating parameters | Electronic torque adjustment | Separate electronic adjustments of opening and closing speeds | Anti-crushing safety through amperometric detection and encoder management | Electronic torque adjustment with automatic calculation for each point of the stroke (STC SYSTEM | Adjustable slowdowns in opening and closing Built-in energy saving system ESA+ | Set up for connection to KNX systems via X.BE card (optional) | Designed for managing, configuring, diagnosing and updating firmware through the BeUP app, using the PRO.UP accessory | Advantouch system to configure parameters and manage radio transmitters Number of manoeuvres | Programming access password | Maintenance warning | Built-in battery charger, compatible with 2 batteries 12V 1.2Ah







Accessory equipped with 1.2 Ah batteries and support bracket.



X.BE

Electronic interface board between the KNX communication system and Benincà automation devices.



PRO.UP

Interface for remote programming and diagnostics.

AUTOMATISMI BENINCÀ SpA • Via del Capitello, 45 • 36066 Sandrigo (VI) ITALY • T +39 0444 751030 • sales@beninca.com

