



TO.GO VA

BENINCA
100%
Made in Italy

TRANSMITTERS WITH DOUBLE CODING, ADVANCED ROLLING CODE AND ROLLING CODE

2 and 4 channels



Configuration and list of available channels (ARC only):

	CH1		CH5
	CH2		CH6
	CH3		CH7
	CH4		CH8
	hidden button		CH9

- 2 or 4-channel transmitter with double coding, Advanced Rolling Code and Rolling Code.
- The new ARC coding guarantees maximum security due to the length of the transmitted code (128 bit) and the high number of possible combinations
- The transmitter has ARC coding as factory setting. However, it is possible to change the coding by using it in Rolling Code or even in mixed coding (ARC and Rolling Code)
- If using mixed coding, the ARC can be set with the T1/T3 buttons and the Rolling Code with the T2/T4 buttons
- The TO.GO4VA model allows users to set up to 9 channels, thanks to the option of activating the command by simultaneously pressing two buttons chosen by the user. This function allows avoiding accidental openings caused by pressing a button by mistake and is particularly indicated for use with alarm systems
- Equipped with 12 V battery for long lifespan
Long range, up to 230 m in a free area
- Car accessory (TO.CLIP) or wall accessory (SMART) available



Training

Guide to memorisation of a TO.GO transmitter in a receiver or control unit and how to change the code. Watch the video.

AUTOMATISMI BENINCA SpA • Via del Capitello, 45 • 36066 Sandrigo (VI) ITALY • T +39 0444 751030 • sales@beninca.com



ONE.2WO

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code, Rolling Code and Fixed Code, with outdoor IP54 box. 512 memorisable codes.



ONE.2WB

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code and Rolling Code, in box. 512 memorisable codes.



ONE.2WI

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code and Rolling Code, plug-in. 512 memorisable codes.



ONE.4WB

4-channel receiver with full-range power supply (115-230 VAC/DC) and triple coding: Advanced Rolling Code, Rolling Code and Fixed Code, with outdoor IP54 box. 512 memorisable codes.



ONE.2QB

Universal 868 MHz receiver, 2 channels, in box.



MEM2048

Additional memory for up to 2048 codes. For receivers of the ONE series.

**TO.GO2VA**

2-channel transmitter with Advanced Rolling Code and Rolling Code.


**TO.GO4VA**

4-channel transmitter with Advanced Rolling Code and Rolling Code.


**TO.GO2QV**

2-channel 868 MHz transmitter with Rolling Code.


AUTOMATISMI BENINCA SpA • Via del Capitello, 45 • 36066 Sandrigo (VI) ITALY • T +39 0444 751030 • sales@beninca.com

**AWO**

433.92 MHz antenna for external installation with IP54 box, fitted with shielded RG58 5 m cable.

**RG58 MT5**


AWO antenna cable L = 5 m.

**AW**

433.92 MHz stylus antenna for external installation, equipped with a shielded 3m RG58 cable.

**SMART**

Cover compatible with TO.GO transmitters for internal wall mounting.

**TO.CLIP**

Car accessory for TO.GO transmitters.

**BT12**

12 V Battery, for transmitter.
Available in 50 pcs packing.